



MAD BAR 4816



OUTPUT

- **LAMP** : 48 PCS 5050 HIGH BRIGHTNESS EPISTAR RGB LED
- **BEAM ANGLE** : 120°
- **CCT** : 2700-6500K
- **LIFE TIME**: 50000 HRS

CONTROL

- **DIMMER** : 0-100% LINEAR LIGHT DIMMING
- **STROBE** : 0-20 F/S, RANDOM OR PULSE, SPEED ADJUSTABLE
- **CONTROL MODE** : DMX512
- **DMX CHANNELS** : 48 CHANNELS
- **ADDRESS SETTING** : AUTO ADDRESSING
- **PIXEL** : 16 PIXEL IN 1 METER

ELECTRICAL

- **INPUT VOLTAGE** : DC 24V
- **POWER** : 10W

PHYSICAL

- **DIMENSIONS** : 1000*28*25 MM
- **WEIGHT** : 0.5 KG



LISTING

- **WORK ENVIRONMENT** : 0-40° DEGREES
- **IP RATE** : IP67

ACCESSORIES

- **CABLING** : 4 PIN MALE FEMALE ATTACHED WITH BAR

MAD BAR 6020



OUTPUT

- **LAMP** : 60 PCS 5050 HIGH BRIGHTNESS EPISTAR RGB LED
- **BEAM ANGLE** : 120°
- **CCT** : 2700-6500K
- **LIFE TIME**: 50000 HRS

CONTROL

- **DIMMER** : 0-100% LINEAR LIGHT DIMMING
- **STROBE** : 0-20 F/S, RANDOM OR PULSE, SPEED ADJUSTABLE
- **CONTROL MODE** : DMX512
- **DMX CHANNELS** : 60 CHANNELS
- **ADDRESS SETTING** : AUTO ADDRESSING
- **PIXEL** : 20 PIXEL IN 1 METER

ELECTRICAL

- **INPUT VOLTAGE** : DC 24V
- **POWER** : 12W

PHYSICAL

- **DIMENSIONS** : 1000*28*25 MM
- **WEIGHT** : 0.5 KG

LISTING

- **WORK ENVIRONMENT** : 0-40° DEGREES
- **IP RATE** : IP67

ACCESSORIES

- **CABLING** : 4 PIN MALE FEMALE ATTACHED WITH BAR